



	TOPFOOD	EVO6inverter	EC06	EC04
Inputs	N°3 NTC [-49.9...+99.9]°C N°3 Digital N°1 4-20mA for humidity probe	N°3 NTC [-49.9...+99.9]°C N°2 Digital inputs	N°3 NTC [-49.9...+99.9]°C N°2 Digital inputs	N°2 NTC [-49.9...+99.9]°C N°1 Digital input
Relays outputs	30-16-16-5-5-5 A	30-5-5-5-5-5 A	30-5-5-5-5-5 A	30-5-5-5 A
Drivers	Electric key Led bar (max 25W)	0-10V evaporator fans 0-10V condenser fans		
Ports	2 x Canbus	2 x Canbus	2 x Canbus	2 x Canbus
Power supply	12Vac - 50/60Hz	230Vac - 50/60Hz	230Vac - 50/60Hz	230Vac - 50/60Hz
Dimensions	156x87x40 mm	168x87x45 mm	156x87x38 mm	110x87x38 mm
Digital logic	One microcontroller	One microcontroller	One microcontroller	One microcontroller
Cut-off relais	No	No	No	No
Sensors	Power supply voltage Board temperature	Power supply voltage Board temperature	Power supply voltage Board temperature	Power supply voltage Board temperature
Compatible RFID reader	No	No	No	No
Compatible displays	D1 - D2 - D3 - D4	D2	D1 - D2 - D3 - D4	D1 - D2 - D3 - D4
CODES				
With din bar support:	BT92201000		BT92204000	
Without box:	BT92201100	BT92204200	BT92204100	BT92205100